

DA-ES1104B

4-Bay eSATA Storage/ NDA Compliant Compatible Recorder : [NVR] DR-2304P(-A)/2308P(-A)/2316P(-A), DR-4308P/4316PS, DR-6308P(-S)/6316PS(-S)/6332PS(-S), DR-6308P(-S)A/6316PS(-S)A/6332PS(-S)A, DR-2404P(-A), DR-6508P/6516P/6532P, DR-8416/8432/8432D, DR-8516/8532/8532D [TVI Recorder] TR-4408(R)/4416(R)



- 19 inch rack-mount
- Maximum of 3.0Gbps transfer rate (SATA II)
- Easy expansibility to a very large storage pool
- Supports RAID Levels 0, 1+ 0, 5
- Installation of the maximum of four hard disk drives
- Compatible Recorder: [NVR] DR-2304P(-A)/2308P(-A)/2316P(-A), DR-4308P/4316PS, DR-6308P(-S)/6316PS(-S)/6332PS(-S), DR-6308P(-S)A/6316PS(-S)A/6332PS(-S)A, DR-2404P(-A), DR-6508P/6516P/6532P, DR-8416/8432/8432D, [TVI Recorder] TR-4408(R)/4416(R)
- SATA to SATA Port Multiplier
- Maximised space saving and capacity relative to the cost

SPECIFICATIONS

Hardware	
Interface	eSATA x1
Number of Drives	SATA II x4
Drive Size	3.5"
Drive Type	SATA II
Supported Device	[NVR] DR-2304P(-A)/2308P(-A)/2316P(-A), DR-4308P/4316PS, DR-6308P(-S)/6316PS(-S)/6332PS(-S), DR-6308P(-S)A/6316PS(-S)A/6332PS(-S)A, DR-2404P(-A), DR-6508P/6516P/6532P, DR-8416/8432/8432D, [TVI Recorder] TR-4408(R)/4416(R)
Performance	
Type and Rate	SATA II(3Gbps)
RAID	0,1+0,5
Max Drive Capacity	16TB(up to 4TB per bay)
General	
Dimensions(W x H x D)	480mm x 44mm x 346mm (18.9" x 1.7" x 13.6")
Weight	6.4kg (14.1lb)
Operating Temperature	0°C to 40°C (32°F ~ 104°F)
Power Input	100V ~ 240VAC, 0.6-0.3A, 50/60Hz
Power Consumption	100-240V~, 50/60Hz, 0.6-0.3A, 40W
Approvals	FCC,CE



PRODUCT IMAGE



DIMENSIONS

(Unit - mm)

