

DA-PI PoE75U

Single Port High-PoE Injector



- Up to 75W of PoE Power
- Protects low power devices to receive only the power they need
- Compatible with IDIS High-PoE IP cameras
- Automatic detection and protection of non-standard Ethernet terminals
- Compatible with IEEE 802.3af, IEEE 802.3at
- Support 10/100/1000 Base-T Lan environment

SPECIFICATIONS

RJ45 Ethernet Interface...DATA In	
port	1 ch
Connectivity	RJ45, Auto-MDI/MDI-X sensing
Wire Type	CAT5 or better
Distance	Up to 100m
Transfer Speed	10/100/1000Mbps
RJ45 Ethernet Interface...PoE	
port	1 ch
Pin Assignment and Polarity	OUTPUT #1(OUT) 3/6(+),1/2(-) OUTPUT #2(OUT) 4/5(+),7/8(-)
PSE Power	56V DC, Max. 75W
Distance	Up to 100m
Speed	10/100/1000Mbps
General	
Dimensions(W x H x D)	80mm x 44mm x 166mm (3.1" x 1.7" x 6.5")
Weight	500g (1.10lb)
Operating Temperature	-20°C ~ +40°C (-4°F ~ 104°F)
Power Input	100 ~240V AC, 50/60Hz, 1.2A
Approvals	FCC, CE ,UL



PRODUCT IMAGE

