

# DH-2010P

## DirectIP® PoE Switch



- Individual port for data transmission to DirectIP® NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 70W available for 1~8 RJ45 ports
- Central power control for greater network utility
- Supports 10 RJ45 ports

### SPECIFICATIONS

System	
CPU	Embedded MIPS
System Memory	256MB SDRAM, 32MB Flash
Switching Capacity	5.6Gbps
Connectivity	
Copper Service Port	8 RJ45 Connectors (10/100BASE-T)
Copper Uplink Port	2 RJ45 Connectors (10/100/1000BASE-T)
Optical Uplink Port	none
PoE Power	
supported Standards	IEEE 802.3af-2003 / IEEE 802.3at-2009
PD Connection	Up to 8 IEEE 802.3af PDs or up to 2 IEEE 802.3at PDs
PSE Power Budget	70W
General	
Dimensions(W x H x D)	280mm x 44mm x 180mm (11.0" x 1.7" x 7.1")
Weight	1.35Kg (2.97lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	AC100-240V, 2.0-1.0A, 50/60Hz
Power Consumption	90W
Approvals	FCC,CE,KC,U.L,CB



### PRODUCT IMAGE



### DIMENSIONS

