

DH-2026PF

24 Port PoE switch



- Individual port data transmission to DirectIP™ NVR
- PoE (IEEE 802.3af, IEEE 802.3at) compliant
- Maximum per-device PoE delivery of 360W available for 1~24 RJ45 ports
- Central power control for greater network utility
- Supports 24 FE RJ45 ports and Uplink 2 GbE RJ45 / 2 GbE SFP combo slots

SPECIFICATIONS

| | |
|------------------------|--|
| System | |
| System Memory | 32MB SDRAM, 16MB Flash |
| Switching Capacity | 8.8Gbps |
| Connectivity | |
| Copper Service Port | 24 RJ45 Connectors (10/100BASE-T) |
| Optical Uplink Port | 2 RJ45 / SFP combo (10/100/1000BASE-T/1000BASE-X) |
| PoE Power | |
| supported Standards | IEEE 802.3af-2003 / IEEE 802.3at-2009 |
| PD Connection | Up to 24 IEEE 802.3af PDs or Up to 12 IEEE 802.3at PDs |
| PSE Power | 360W |
| General | |
| Diemensions(W x H x D) | 430mm x 44mm x 235mm (17.0" x 1.7" x 9.3") |
| Weight | 2.62Kg (5.77lb) |
| Operating Temperature | 0°C - 40°C (32°F - 104°F) |
| Power Input | 100-240V~, 50/60Hz, 5.0-2.5A, 450W |
| Power Consumption | 450W |
| Approvals | FCC, CE, KC, UL, CB |



PRODUCT IMAGE



DIMENSIONS

(Unit - mm)

