

NK-1200

Network Keyboard



Remote control of NVRs, network video

- transmitters, network video receivers and network cameras via the network connection
- Convenient firmware upgrades via either the USB port or Ethernet
- Programmable by using the LCD screen
- Two-way audio communication
- Firmware duplication and auto-recovery functions to enhance system stability
- Two-way audio communication
- Management of multiple network keyboards via the network connection

SPECIFICATIONS

Communication	
Interface	2 x RS485(Terminal Block), 10/100/1000 Ethernet(RJ45, PoE IEEE802.3af)
Baud Rate	300 bps ~ 11,200bps
Supports protocols	Over 70 sorts of PTZ protocol(IDIS, PANASONIC, PELCO, SAMSUNG, etc.)
Supports Devices	IP Camera, NVR, IDIS solution Suite
Display	LCD(2 Line)
USB	1x USB2.0, 1x USB3.0
Audio in/out	1(3.5mm) / 1(3.5mm)
configuration	Joystick + Main Control Board
S/W Upgrade	USB, Network
SETUP Program	IDIS Discovery
General	
Dimension(W x H x D)	376.9mm x 95mm x 177.6mm (15.0" x 3.7" x 7.0")
Unit Weight(Kg)	1.1kg (2.43lb)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	DC 48V, 1A, PoE(IEEE 802.3af class 0)
Approvals	FCC, CE, KC



PRODUCT IMAGE



DIMENSIONS